

Technical Data Sheet

Vision Vantage Display FR

Material	100% Polyester		
Stock widths	253cm / 320cm		
Weight			
acc. to DIN EN 12127	220.00	[g/m ²]	+ - 3 [%]
Ecology	According to Öko-Tex Standard 100, product class 2		
Weight			
acc. to DIN EN 12127	220.00	[g/m ²]	+ - 3 [%]
Shrinkage			
Heat Shrinkage, 195 °C, 90 sec, lengthwise			
acc. to AA 25-02	-2.50	[%]	+ - 1 [%]
Heat Shrinkage, 195 °C, 90 sec, crosswise			
acc. to AA 25-02	-2.50	[%]	+ - 1 [%]
Tearing strength			
Maximum tensile elongation, longitudinal direction			
acc. to DIN EN ISO 13934-1	45.00	[%]	+ - 20 [%]
Maximum tensile elongation, cross direction			
acc. to DIN EN ISO 13934-1	50.00	[%]	+ - 20 [%]
Maximum tearing strength, longitudinal direction			
acc. to DIN EN ISO 13934-1	min. 350.00	[N/5 cm]	
Maximum tearing strength, cross direction			
acc. to DIN EN ISO 13934-1	min. 850.00	[N/5 cm]	
Continuing tearing strength, longitudinal direction (Durchschnittswert)			
acc. to DIN EN ISO 13937-2	30.00	[N]	+ - 10 [%]
Continuing tearing strength, cross direction (Durchschnittswert)			
acc. to DIN EN ISO 13937-2	20.00	[N]	+ - 10 [%]
Fire Retardancy	EN13501 / B1		



MADE IN
GERMANY