

Vision Recycled Flag



dpm
digital print media

Technical Data Sheet

Vision Recycled Flag

With INKTeX+BS® finishing for direct print, with flame retardant treatment, tested to EN13501.

Material	100 % Recycled Polyester made of REvive polyester, because of the recycling process the degree of whiteness differs from production to production
Stock widths	app. 320 cm,
Finishing	Rolled on paper cores
Ecology	According to Öko-Tex Standard 100, product class IV

Weight				
acc. to DIN EN 12127	110.00	[g/m²]	+ - 5	[%]
Shrinkage				
Heat Shrinkage, 195 °C, 90 sec, lengthwise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Heat Shrinkage, 195 °C, 90 sec, crosswise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Tearing strength				
Maximum tensile elongation, longitudinal direction				
acc. to DIN EN ISO 13934-1	5.00	[%]	+ - 20	[%]
Maximum tensile elongation, cross direction				
acc. to DIN EN ISO 13934-1	20.00	[%]	+ - 20	[%]
Maximum tearing strength, longitudinal direction				
acc. to DIN EN ISO 13934-1	min. 320.00	[N/5 cm]		
Maximum tearing strength, cross direction				
acc. to DIN EN ISO 13934-1	min. 540.00	[N/5 cm]		



Roseash Limited , Unit F, Field Way, Metropolitan Park, Greenford, UB6 8UN
T : 0203 264 1000 F : 0203 264 1010 E : sales@dpm.com W : www.dpm.com