

Vision Vesta Weave



dpm
digital print media

Technical Data Sheet

Vision Vesta Weave

With INKTeX+BS® finishing for direct print, with flame retardant treatment,

Material	100 % Polyester
Stock widths	310 cm
Finishing	Rolled on paper cores
Ecology	Öko-Tex Standard 100, product class IV

Weight				
acc. to DIN EN 12127	115.00	[g/m ²]	+ - 3	[%]
Shrinkage				
Heat Shrinkage, 195 °C, 90 sec, lengthwise				
acc. to AA 25-02	max. -2.00	[%]	+ - 1	[%]
Heat Shrinkage, 195 °C, 90 sec, crosswise				
acc. to AA 25-02	max. -2.00	[%]	+ - 1	[%]
Tearing strength				
Maximum tensile elongation, longitudinal direction				
acc. to DIN EN ISO 13934-1	45.00	[%]	+ - 20	[%]
Maximum tensile elongation, cross direction				
acc. to DIN EN ISO 13934-1	45.00	[%]	+ - 20	[%]
Maximum tearing strength, longitudinal direction				
acc. to DIN EN ISO 13934-1	min. 250.00	[N/5 cm]		
Maximum tearing strength, cross direction				
acc. to DIN EN ISO 13934-1	min. 260.00	[N/5 cm]		
Air Permeability				
acc. to DIN EN ISO 9237	3900.00	[l/m ² s]	+ - 10	[%]
Fire Retardancy	B1			



Roseash Limited , Unit F, Field Way, Metropolitan Park, Greenford, UB6 8UN
T : 0203 264 1000 F : 0203 264 1010 E : sales@dpm.com W : www.dpm.com