

# Vision Digi Flag



**dpm**  
digital print media

## Technical Data Sheet

### Vision Digi Flag

With INKTeX+BS® finishing for direct print, with flame retardant treatment, tested to EN13501.

Material	100 % Polyester			
Stock widths	app. 320 cm,			
Finishing	Rolled on paper cores			
Ecology	According to Öko-Tex Standard 100, product class I			
Weight				
acc. to DIN EN 12127	110.00	[g/m <sup>2</sup> ]	+ - 3	[%]
Shrinkage				
Heat Shrinkage, 195 °C, 90 sec, lengthwise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Heat Shrinkage, 195 °C, 90 sec, crosswise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Tearing strength				
Maximum tensile elongation, longitudinal direction				
acc. to DIN EN ISO 13934-1	25.00	[%]	+ - 20	[%]
Maximum tensile elongation, cross direction				
acc. to DIN EN ISO 13934-1	50.00	[%]	+ - 20	[%]
Maximum tearing strength, longitudinal direction				
acc. to DIN EN ISO 13934-1	min. 320.00	[N/5 cm]		
Maximum tearing strength, cross direction				
acc. to DIN EN ISO 13934-1	min. 620.00	[N/5 cm]		
Air Permeability				
acc. to DIN EN ISO 9237	1900.00	[l/m <sup>2</sup> s]	+ - 10	[%]
Flame Retardency	B1			



Roseash Limited , Unit F, Field Way, Metropolitan Park, Greenford, UB6 8UN  
T : 0203 264 1000 F : 0203 264 1010 E : sales@dpm.com W : www.dpm.com